

**NRL709GB 磁保持继电器 /Magnetic Latching Relay**



◆ **特点 Characteristic**

- > 100A 触点切换能力；
- > 线圈功耗小，温升极低；
- > 触点接触电阻小，电接触稳定性好；
- > 抗冲击、抗振动能力强；
- > 外形尺寸：135×120×47mm
- > 可根据客户要求焊接锰铜分流器和连接铜线。
- > 100A switching capability.
- > Low coil consumption, ultra-low temperature rise.
- > Low contact resistance.
- > Strong anti-shock and anti-vibration capability.
- > Outline size: 135×120×47mm
- > Customized terminals like shunt, braided Cu- wire etc.

◆ **订货标记 Ordering Information**

NRL	709GB	09	-	S	-	100	①	磁保持继电器代号 Latching Relay
①	②	③	④	⑤			②	产品型号 Part Number
							③	线圈电压 Coil Voltage
							④	D 表示双线圈，S 表示单线圈 D= Double Coil; S= Single Coil
							⑤	100=100A

◆ **性能 Characteristics**

绝缘电阻 Insulation resistance		1000MΩ (500VDC)
介质耐压 Dielectric Strength	触点与线圈间 Between Coil & Contacts	4000VAC 1min
	断开触点间 Between Open Contacts	2000VAC 1min
闭合时间 Operate Time		30msec. Max
断开时间 Release Time		30msec. Max
抗冲击 Shock resistance	稳定性 Functional	100m/S <sup>2</sup> (10g)
	强度 Destructive	1000m/S <sup>2</sup> (100g)
振动 Vibration resistance		10~55Hz 1.5mm
湿度 Humidity		95%RH ,40°C
温度范围 Ambient temperature		-40 ~ +70°C
引出端方式 Termination		快连接式 Fast connection
重量 Unit weight		700g
封装形式 Constrution		防尘罩 Dust protected

## NRL709GB 磁保持继电器 /Magnetic Latching Relay

## ◆ 触点参数 Contact Data

触点形式 Contact form	3A/3B
触点材料 Contact material	AgSnO <sub>2</sub>
接触电阻 Contact resistance	Max: 1.0mΩ
触点负载 Contact Rating	100A 250VAC
最大转换功率 Max. Switching Power	25000VA
机械寿命 Mechanical life	1×10 <sup>5</sup>
电气寿命 Electrical life	1×10 <sup>4</sup>

## ◆ 线圈 Coil

线圈功耗 Coil power	单线圈 : 5.1W 双线圈 :10.2W Single coil: 5.1W Double coil: 10.2W
-----------------	---

## ◆ 线圈参数 Coil Data

额定电压 (VDC) Rated Voltage	动作电压 (VDC) Pick-up voltage	脉冲宽度 (ms) Pulse Duration	线圈电阻 (Ω) Coil Resistance
单线圈 Single coil			
9	6.8	100	16±10%
12	9	100	28±10%
16	18	100	50±10%
24	36	100	113±10%
双线圈 Double coil			
9	6.8	100	2×8±10%
12	9	100	2×14±10%
16	18	100	2×25±10%
24	36	100	2×56.5±10%

备注：如需其它额定电压，可特殊定货。

Note: Special ordering for other coil voltage.

## ◆ 典型应用 Typical Application

- 1) 主要用于 IC 卡预付费电表，集中抄表系统；  
Prepayment Energy Meter; AMR System;
- 2) 也用于复合开关、家电和自动控制装置。  
Compound Switch; Automatic Control System.

NRL709GB 磁保持继电器 / Magnetic Latching Relay

◆ 尺寸图 Dimensions(mm)/ 接线图 Circuit Diagram

